

ALLOWABLE RANGE OF ADJUSTMENT
PER CITY OF MIDDLETON SPECIFICATIONS

ADJUSTMENT HEIGHT	ADJUSTMENT RING COMBINATIONS
4.00"	2.00"+2.00"
4.50"	1.50"+1.50"+1.50"
5.00"	1.50"+1.50"+2.00"
5.50"	1.50"+4.00"
6.00"	2.00"+4.00"
6.50"	1.50"+1.50"+1.50"+2.00"
7.00"	1.50"+1.50"+4.00"
7.50"	1.50"+2.00"+2.00"+2.00"
8.00"	4.00"+4.00"
8.50"	1.25"+1.25"+2.00"+4.00"
9.00"	1.50"+1.50"+2.00"+4.00"
9.50"	1.50"+4.00"+4.00"
10.00"	2.00"+4.00"+4.00"
10.50"	1.50"+1.50"+1.50"+2.00"+4.00"
11.00"	1.5"+1.50"+4.00"+4.00"
11.50"	1.5"+2.00"+4.00"+4.00"
12.00"	2.00"+2.00"+4.00"+4.00"

NOTE:

MANUFACTURE APPROVED SEALANT SHALL BE
BE APPLIED BETWEEN ADJUSTMENT RINGS



CITY OF MIDDLETON
STANDARD DETAIL

INLET ADJUSTMENT RING
SIZE COMBINATIONS

REVISED 10-21-2014
DRAWN BY: TCF

300-04